ULTRA TREMOLO UT300

Classic Tremolo Effects Pedal

Thank you for showing your confidence in us by purchasing the BEHRINGER ULTRA TREMOLO UT300. This high-quality effects pedal is designed to provide guitarists easy-to-use tremolo effect styles. Thanks to its high-performance features you get the classic, warm and mind-bending tremolo effects of vintage '60s amps.

The tremolo effect is achieved by periodic modulation of the input signal level. This results in a continuous change from low to high level that has a quivering, tremulous sound character.

1. Controls



- 1 The **RATE** control adjusts the speed of the tremolo effect.
- 2 The **DEPTH** control adjusts the intensity of the effect.
- The WAVE control alters the LFO waveform that modulates the input signal from triangle to square. This way you can achieve practically any tremolo sound, from classic to radical styles.
- 4 The **ON/BATT** LED illuminates when the effect is activated. It also serves as a battery level indicator.
- Use the footswitch to activate/deactivate the effect.
- 6 Use this ¼" TS **IN** connector to plug in the instrument cable.
- The ¼" TS **OUT** connector sends the signal to your amp.

Use the **DC IN** connection at the front of the unit to plug in a 9 V power supply (not included).

The **BATTERY COMPARTMENT** is located underneath the pedal cover. To install or replace the 9 V battery, press the hinges with a ballpen and remove the pedal cover. Be careful not to scratch the unit.

The UT300 has no on/off switch. As soon as you insert the jack into the in connector, the UT300 begins running. When not using the UT300, remove the jack from the in connector. This extends the life of the battery.

The SERIAL NUMBER is located at the bottom.



2. Safety Instructions

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

3. Warranty

Please register your new BEHRINGER equipment right after your purchase by visiting http://behringer.com and read the terms and conditions of our warranty carefully.

4. Specifications

In	
Connector	1⁄4" TS
Impedance	500 kΩ
Out	
Connector	1⁄4" TS
Impedance	1 kΩ
Power Supply	
,,,	9 V⋯, 100 mA regulated
BEHRINGER PSU-SB	
USA/Canada	120 V∼, 60 Hz
U.K./Australia	240 V∼, 50 Hz
China/Korea	220 V∼, 50 Hz
Europe	230 V∼, 50 Hz
Japan	100 V∼, 50 - 60 Hz
Power connector	2 mm DC jack,
	negative center
Battery	9 V type 6LR61
Power consumption	30 mA
Physical/Weight	
Dimensions	approx. 2 1/8 x 2 3/4 x 4 4/5"
(H x W x D)	approx. 54 x 70 x 123 mm
Weight	approx. 0.73 lbs / 0.33 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUIARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP COMP. ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HERRIC. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP PAND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTRAINS OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLIDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTED IN PRIMISSION OF MUSIC GROUP IP LTD. ALL RIGHTS RESERVED. © 2012 MUSIC Group IP Ltd. Trident Chambers, Wickhams Cay, P.O. Box 146, Road Town, Tortola, British Virgin Islands

