

Product Detail Page



CLUB-1TOP

Number: 25.2490

The CLUB system from IMG Stage Line: compact full range speaker, subwoofer and amplifier perfectly matched to each other and in combination provide a top-quality performance and considering the dimensions and price, they are simply fascinating! The units of the CLUB series from IMG Stage Line provide unique possibilities, whether applied individually or together with other PA products of highest quality! Pair of professional PA speaker systems, 2 x 160W_{MAX}, 2 x 100W_{RMS}/8 Ω

An extra compact PA speaker system of perfect quality, suitable for applications in trendy bars and restaurants, music cafés, in lounges, bars and clubs as well as for PA application of highest requirements in adjoining areas of discotheques. In combination with the CLUB-1SUB and the STA-1603CLUB, a full-range system of amazingly high volume levels can be created, too. Furthermore, it is also ideally suited as a mobile system, both for announcements and presentations. With a subwoofer addition, it is also suitable for DJ applications. High-quality lacquered MDF cabinet with full front grille cased with acoustic foam. Six thread inserts (M8) and a standard stand sleeve at the bottom for really universal mounting possibilities. Configuration: a high-performance 16cm bass-midrange speaker with carbon fibre cone and a waveguide dome tweeter for an absolutely undistorted reproduction of the high frequencies. Perfect tonality for a pleasant perception of the music and precise speech intelligibility at all levels. SPEAKER IN/OUT for an easy parallel connection. The shape and size of the CLUB-1TOP are designed in such a way that the ambience of the location is still maintained even in larger rooms with a decentralised arrangement of several speakers for acoustic reasons. For driving the system, an amplifier STA-1503CLUB is perfectly suitable at which 1, 2, 4 or even 8 CLUB-1TOP speakers can be operated per mid-high range channel (4 or 8 in corresponding series/parallel circuits). The power capability of the amplifier is quite high when connecting one or two speakers, but the volume capability of the speakers is still almost fully utilised when connecting 8 speakers. The application of multichannel amplifiers STA-... from IMG Stage Line (STA-1504 to STA-1508) at which up to two CLUB-1TOP speakers per channel can perfectly be operated in parallel may be an alternative. **discret 02/2011**

"Above all, the CLUB system impresses by a sophisticated concept for a high flexibility, reliability and a solid quality with high level reserves. The system surely provides a high power capability, great features and a good workmanship for its price and the sound is more than adequate for many applications in trendy clubs, bars and restaurants, even applications of high requirements. **tools4music 01/2011**

"The CLUB system from IMG Stage Line impresses by a full bass reproduction and pleasant high frequencies. The CLUB system can perfectly be matched to individual requirements and be extended any time by adding further components. The basic equipment already presents an appealing picture." + Compact size + Resistant cabinet + Two Speakon jacks **SOUNDCHECK 10/2010**

"Lightweight top speakers of a compact size with extensive crossover network ... money put on operational reliability!"

"A nice compact size and unobtrusive appearance. A well-balanced bass reproduction, an appealing midrange and a very enjoyable reproduction of the high frequencies - simply very nice. Offers various possibilities for extension."

(on the CLUB system) **Beat 69, 07-08/2011**

"A multi-purpose system showing high stability and reliability in continuous operation. The small satellites provide an assertively pleasant sound. The subwoofers feature a dynamic and full sound. The CLUB system ensures sophisticated, compact and reliable PA applications of high quality at a fair price."



Technical Facts

System	2-way bass-reflex
Bass speaker	16cm (6.5")
Tweeter	dome tweeter with waveguide
Power capabilities	
Music power	160W _{MAX}
Power rating	100W _{RMS}
General information	
Impedance	8 Ω
Frequency range	55-21,000Hz
SPL (1W/1m)	90dB
Max. rated SPL	110dB
Admiss. ambient temp.	0-40 °C
Dimensions	210x300x260mm
Inputs	1 x SPEAKER
Outputs	1 x SPEAKER
Weight	6kg

