

Product Detail Page



PAB-308/WS

Number: 25.4300

The multi-purpose PA speakers of the 300 series from IMG Stage Line are suitable for versatile applications. They can be used for both fixed installations and mobile applications. Ideally suited for powerful PA applications of good level stability in rooms as well as for rearfill applications and sidefill applications. The very compact and easy-to-transport systems are also very well-suited for mobile applications when combined with appropriate subwoofers, e.g. PSUB-12AKA or PSUB-15AKA and as small floor monitors.

Universal PA speaker system, 250W_{MAX}, 8 Ω

- Compact 8/2 full range bass-reflex system
- 20cm (8") bass speaker and 25mm (1") horn tweeter
- High-quality MDF wooden cabinet in black (SW) or white (WS), with metal protective grille
- Multi-purpose positioning and installation options
- 4 x M8 thread inserts for suspended installation
- Supplied with mounting bracket and integrated stand sleeve
- NEUTRIK SPEAKON terminal



Technical Facts

System	2-way bass-reflex
Bass speaker	20cm (8")
Tweeter	25mm (1") horn tweeter
Power capabilities	
Music power	250W _{MAX}
Power rating	125W _{RMS}
General information	
Impedance	8 Ω
Frequency range	60-20,000Hz
SPL (1W/1m)	93dB
Max. rated SPL	115dB
Admiss. ambient temp.	0-40 °C
Dimensions	258x410x247mm
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON, par. out
Weight	7.5kg

